



MULTIFUNCTION UNDERCOUNTER DISHWASHER F94-XL-DY-D-P

Stainless steel construction 18/10 AISI 304. Insulated double skin (thermic and acoustic insulation with a thickness of 14 mm). **Wash cycle time:** 60"-120"-180"-10'; 120"-180"-240"-10'. Extractable soft-touch control panel with interactive graphic display - wash and rinse temperature electronic display, complete programming of all the washing parameters. Rotating lower and upper wash and upper rinse. Constant rinse boiler system (RCB). Rinse-aid dispenser. Economy thermostat. Drawn tank with self-cleaning bottom and rounded edges. Thermocontrol (device which guarantees the selected temperature for every rinsing cycle even in case of nonstop work). Cycle start with soft-start system. Integral tank drawer filters. Automatic tank loading. Door opening safety device. Suitable to wash crates, containers, baking-pans, kitchen utensils and whatever kind of dishes and glasses. **Cpl. with** detergent pump and drain pump.

ACCESSORIES

1 general basket in plastic with two open sides, 1 baking pan rack for 3 trays in S.S., 1 basket for 22 dishes in plastic, 1 general basket in plastic, 2 cutlery containers in plastic

NEW CONTROL PANEL WITH INTERACTIVE GRAPHIC DISPLAY

- complete programming of all the washing parameters
- graphic display with description of washing steps
- programming of the timing of detergent and rinse-aid pumps
- cycle counter; service maintenance function
- **disinfection cycle ideal for hospitals!**
- descaling function (option).



Specifications	F94-XL-dy
DIMENSIONS l x w x h, mm	600 x 715 x 890
WASHING CAPACITY baskets/H	30/20/15 60/30/20
WASH CYCLE, min	2+3+4 ∞ 1+2+3 ∞
BASKET SIZE, cm	60 x 50
PLATES PER BASKETS, No.	22
WASHING CAPACITY dishes/H	660/440/330 1320/440/330
WORK HEIGHT, mm	415
CLEARANCE, mm	400
VOLTAGE	400 B 3N-50 Гц
ELECTRIC PUMP, W	650
WASH TANK ELEMENTS, W	2000
RINSE TANK ELEMENTS, W	6000
TOTAL RATING, W	6650
MAX CURRENT INTENSITY, A	10
TANK CAPACITY, l	18
BOILER CAPACITY, l	5
RINSE AID DISPENSER	✓
WATER CONNECTION, °C	45 ÷ 55
PUMP DELIVERY, l/min	300
CYCLE WATER CONSUMPTION, l	2,60
HOURLY WATER CONSUMPTION, l	52
WATER PRESSURE, bar	2 ÷ 4
RINSING WATER TEMPERATURE, °C	80 ÷ 90
WATER INLET, "G	3/4"
WATER OUTLET, "G	32 mm ÷ 1"1/4
NET WEIGHT, kg	82
GROSS WEIGHT, kg	93
NOISE, dB(A)	<54

Standard	
DOUBLE SLIDE TO WASH CUPS AND SAUCERS SIMULTANEOUSLY	
Options	
TIMED DISPENSER FOR LIQUID DETERGENT	
TANK DRAIN UNIT WITH FILTER	
STAINLESS STEEL BASE WITH LOWER OPEN PLACE H.575MM	
BOOSTER PUMP	
INCORPORATED WATERSOFTENER WITH AUTOMATIC REGENERATION	F94-XL-dy-add
SAFE RINSE (BREAK TANK)	

